



Exinda SD-WAN enables cost-effective Internet access and network solutions for any size business, apartments, hotels & other multi-tenant buildings. Exinda SD-WAN aggregates the capacity of two or more (or optionally as many as eight or twelve) T-1, DSL or cable modem services and two USB-based cellular data cards. This provides increased access bandwidth for downloaded traffic equal to the combined bandwidth of the aggregated links, even to a single user.

Exinda SD-WAN can provide this higher access capacity and more reliable Internet access at a much lower cost than comparable-bandwidth and expensive fiber optic or T-3 access service. It has a 1U rack-mountable form factor with silent active cooling.



## exinda SD-WAN Features

### ✓ Downlink/Uplink Bonding in Peered Mode

Exinda SD-WAN bonds Internet access lines for all types of traffic (including encrypted traffic such as VPN) for aggregated downlink and uplink capacity. Two appliances can be used in case of multi-site offices or else one can rely on our cloud hosted on Amazon AWS.

### ✓ Aggregated Downlink Capacity in Standalone Mode

When not peered with another Exinda SD-WAN appliance, all HTTP downlink sessions use the aggregated bandwidth of the combined Internet access links, even in the case of a single HTTP session. For non-HTTP downlink sessions and all uplink sessions, Exinda SD-WAN provides session-based intelligent load balancing across the access links in standalone mode.

### ✓ Link Failure Recovery & Link Failover

In case of Internet access line failures, the Exinda SD-WAN appliance keeps the ongoing sessions alive by retransmitting the lost packets over the available access lines, even for the sessions in progress, without loss of data integrity. Additionally, automatic failover protects against failures of one or more access link outages. You can add 2G/3G/4G cellular cards as standby WAN access links for additional reliability.

### ✓ Traffic Monitoring & Shaping

You can monitor traffic via graphical plots over seconds/minutes/hours/days/months. Filter and shape various realtime and non-realtime traffic types.

### ✓ Strong AES Encryption

Exinda SD-WAN bonding tunnels have built-in security option with AES 256 encryption.

### ✓ Virtual Interfaces with WAN & Traffic Management

Exinda SD-WAN supports virtual interfaces that have real physical WAN interfaces. Specific types of traffic can then be selectively filtered onto the virtual interface to take advantage of the load-balancing and failover capabilities of the virtual interface.

✓ **Transparent Zero-touch Installation**

The existing Local Area Network does not require any changes. You do not need coordination, new equipment or software from the Internet Service Provider(s). A remotely accessible browser-based interface provides quick and easy management and system monitoring.

✓ **Advanced QoS Algorithms**

All traffic routed through Exinda SD-WAN is intelligently managed to prioritize real-time applications (such as VoIP). Additionally, Exinda SD-WAN implements a unique set of proprietary algorithms to improve inbound real-time traffic latency metrics specifically for VoIP applications.

✓ **Dynamic DNS Load Balancing**

You can configure Exinda SD-WAN to provide Dynamic DNS load-balancing for inbound requests for internally hosted servers such as web-server, FTP-server, mail-server etc.

✓ **Cellular 3G, 4G, LTE WAN Connection**

Exinda SD-WAN supports 2 USB ports for cellular 3G/4G/LTE data cards. The cellular WAN links can be configured as fail-over, or always on.

✓ **Exinda Network Orchestrator Compatibility**

Exinda SD-WAN complements and is fully compatible with Exinda Network Orchestrator for added traffic shaping via application classification as well as acceleration between different sites.



**EXSD-10G****HARDWARE SPECIFICATIONS****Mechanical dimensions**

438(W) x 292.1(D) x 44(H) mm,  
17.25"(W) x 11.5"(D) x 1.73"(H).

**Weight**

10.4lbs.

**Input power requirement**

80 plus 250W full-range ATX.

**USB ports**

2 (for cellular data).

**LAN ports (GbE, auto-sensed)**

2x 10 GbE fiber Ethernet connectors.

**WAN ports (GbE, auto-sensed)**

10x 1GbE copper WAN ports,  
2x 10GbE fiber Ethernet ports.

**Certifications**

FCC, CE, RoHS-2, UL.

**Operating Temperature**

32 – 104 F, 0 – 40 Celsius.

**Operating Humidity Range**

20-90% RH.

**Storage Temperature Range**

14 – 158 F, -10 – 70 Celsius.

**Operating Humidity Range**

15-95%, non-condensing.

**EXSD-10G****SOFTWARE SPECIFICATIONS****Max throughput**

10 Gbps (standalone),  
800Mbps (peered).

**Max No. of concurrent IP sessions**

1,000,000

**Device management**

SNMP, Remote Syslog, Email alerts.

**DHCP and DNS servers**

DNS relay, Parallel DNS  
optimization, DHCP server.

**DDNS**

Support for dynamic DNS for  
multiple interfaces.

**WAN Configuration**

Static IP, PPPoE, DHCP or  
passthrough. Failover-only or  
aggregate modes for cellular and  
other WAN ports. Interface binding.

**Routing**

NAT and IP forwarding, QoS and  
inbound/outbound VOIP quality  
management.



**EXSD-300****HARDWARE SPECIFICATIONS****Mechanical dimensions**

438(W) x 292.1(D) x 44(H) mm,  
17.25"(W) x 11.5"(D) x 1.73"(H).

**Weight**

10.4lbs.

**Input power requirement**

200W full-range ATX.

**USB ports**

2 (for cellular data).

**LAN ports (10/100/1000 baseT, auto-sensed)**

4 RJ45 Ethernet WAN ports. 4 more or 8 more RJ45 Ethernet WAN ports add-on option.

**Certifications**

FCC, CE, RoHS-5, ICES-03, UL, cUL.

**Operating Temperature**

32 – 104 F, 0 – 40 Celsius.

**Operating Humidity Range**

20-90% RH.

**Storage Temperature Range**

-4 – 158 F, -10 – 70 Celsius.

**EXSD-300****SOFTWARE SPECIFICATIONS****Max throughput**

Base: 1Gbps (load balancing), 300 Mbps (standalone) , 100Mbps (peered). Higher performance available in Truffle E, EC, EF models).

**Device management**

SNMP, Remote Syslog, Email alerts.

**DHCP and DNS servers**

DNS relay, Parallel DNS optimization, DHCP server.

**DDNS**

Support for dynamic DNS for multiple interfaces.

**WAN Configuration**

Static IP, PPPoE, DHCP or passthrough. Failover-only or aggregate modes for cellular and other WAN ports. Interface binding.

**Routing**

NAT and IP forwarding, QoS and inbound/outbound VOIP quality management.

**EXSD-1000****HARDWARE SPECIFICATIONS****Mechanical dimensions**

438(W) x 292.1(D) x 44(H) mm,  
17.25"(W) x 11.5"(D) x 1.73"(H).

**Weight**

10.4lbs.

**Input power requirement**

80 plus 250W full-range ATX

**USB ports**

2 (for cellular data).

**LAN ports (GbE, auto-sensed)**

2 GbE copper RJ45 Ethernet connector. One WAN port to LAN port fail-to-wire in case of power outage.

**WAN ports (GbE, auto-sensed)**

8 GbE copper WAN ports (model E).  
Add-on module option for additional:  
8 GbE copper (model EC) or 8 GbE SFP ports (model EF).

**Certifications**

FCC, CE, RoHS-2, UL.

**Operating Temperature**

32 – 104 F, 0 – 40 Celsius.

**Operating Humidity Range**

20-90% RH.

**Storage Temperature Range**

-4 – 158 F, -10 – 70 Celsius.

**EXSD-1000****SOFTWARE SPECIFICATIONS****Max throughput**

1Gbps (load balancing), 940 Mbps (standalone) , 800Mbps (peered).

**Max No. of concurrent IP sessions**

1,000,000

**Device management**

SNMP, Remote Syslog, Email alerts.

**DHCP and DNS servers**

DNS relay, Parallel DNS optimization, DHCP server.

**DDNS**

Support for dynamic DNS for multiple interfaces.

**WAN Configuration**

Static IP, PPPoE, DHCP or passthrough. Failover-only or aggregate modes for cellular and other WAN ports. Interface binding.

**Routing**

NAT and IP forwarding, QoS and inbound/outbound VOIP quality management.